

# Material Safety Data Sheet (MSDS)

## UV Westacure Texture RC Gloss Top Coat - BG

**Product Code-WCO/10156**

### **Section 1: Chemical Product and Company Identification**

Product Name: UV Westacure Texture RC Gloss Top Coat-BG

Chemical Name: N/A

Chemical Formula: N/A

Manufacturer Name & Address

Westtek Enterprises Private Limited

Manipal-576104

Karnataka, India

### **Section 2: Hazards Identification**

Indication of danger

Xi: Irritant



Risk advice to man and the environment

R36/38 Irritating to eyes and skin.

R43 May cause sensitization by skin contact.

R52/53 Harmful to aquatic organisms may cause long-term adverse effects in the aquatic environment

### **Section 3: Composition/Information on Ingredients**

Chemical Name	CAS-No.	Symbol(s)	R-phrase(s)	Concentration [%]
Acrylates	71281-65-7	Xi	R36/38	>= 20,00 - < 25,00
Acrylate-Monomers	57472-68-1	Xi	R36/38, R43	>= 20,00 - < 25,00
Acrylate- Monomers	42978-66-5	Xi	R36/38, R43	>= 20,00 - < 25,00
Acrylate- Monomers	15625-89-5	Xi	R36/38, R43	>= 7,00 - < 10,00
Benzophenone	119-61-9	N	R50/53	>= 7,00 - < 10,00
Ketones		Xi	R52/53	>= 7,00 - < 10,00
Darocure 1173	7473-98-5	Xi	R38 R41 R43	>= 1,00 - < 3,00
Reactive Tertiary Amine		Xi	R38 R41 R43	>= 1,00 - < 3,00

**Chemical Nature:**

Printing Ink

**Additional advice:**

For the full text of the R-phrases mentioned in this Section, see Section 16.

For information about ingredients with occupational exposure limits see section 8.

**Section 4: First Aid Measures**

- Inhalation : Remove to fresh air.  
If symptoms persist, call a physician.
- Skin contact : Take off all contaminated clothing immediately.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
DO NOT use solvents or thinners.
- Eye contact : Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.  
Remove contact lenses.  
Seek medical advice.
- Ingestion : If accidentally swallowed obtain immediate medical attention.  
DO NOT induce vomiting.

**Section 5: Fire Fighting Measures**

- Suitable extinguishing media : Alcohol resistant foam, CO2 and powders
- Extinguishing media which shall not be used for safety reasons : High volume water jet
- Specific hazards during fire fighting : Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.  
Wear self contained breathing apparatus for firefighting if necessary.  
Fire will produce dense black smoke containing hazardous combustion products (see section 10).

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

## **Section 6: Accident Release Measure**

Personal precautions : Ventilate the area.  
Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Do not let product enter drains.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local regulations.  
Clean preferably with a detergent.  
Avoid use of solvents.

## **Section 7: Handling and Storage**

### **Handling**

Advice on safe handling : Avoid exceeding of the given occupational exposure limits (see section 8).  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Avoid contact with skin, eyes and clothing.

### **Storage**

Requirements for storage areas and containers : Never apply pressure on container.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Keep container tightly closed in a dry cool and well-ventilated place.  
Observe label precautions.

Further information on storage conditions : Keep away from heat and direct sunlight.  
Store in accordance with the particular national regulations concerning water pollution.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

**Section 8: Exposure Control /personal protection**

The Netherlands MAC (Maximum Aanvaarde Concentratie)	150 mg/m <sup>3</sup> (MAC) 40 ppm (MAC)
Germany MAK (Maximale Arbeitsplatzkonzentration)	50 ppm (TWA) 190 mg/m <sup>3</sup> (TWA) 50 ppm (OEM-TWA)
United Kingdom MEL(Maximum Exposure Limits)	50 ppm (OES-TWA) 191 mg/m <sup>3</sup> (OES-TWA) 574 mg/m <sup>3</sup> (OES-STEL) 150ppm (OES-STEL)
France: VLEP (Valeur Limited dExposition Professionnelle)	375 mg/m <sup>3</sup> (VME) 100 ppm (VEM) 550 mg/m <sup>3</sup> (VLE) 150 ppm (VLE)
Denmark: Graensevaerdier	94 mg/m <sup>3</sup> (TWA) 25 ppm (TWA) (skin)
Norway:	25 ppm (TWA-OEL) 94 mg/m <sup>3</sup> (skin)
Sweden: Hygieniska Gransvarden	50 ppm (LLV) 200 mg/m <sup>3</sup> (LLV) 100 ppm (STV) 400 mg/m <sup>3</sup> (STV) (skin)
ACGIH (TLV)	50 ppm (TWA) (skin)

**Engineering measures:**

Utilize a closed System process where feasible.

Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure.

**Respiratory protection:**

For operations where inhalation exposure can occur, use an approved respirator recommended by an industrial hygienist after an evaluation of the operation. Where inhalation exposure cannot occur, no respiratory protection is required. A full face peace respirator also provides eye and face protection.

**Eye protection:**

Prevent eye and skin contact.

Provide eye wash fountain and safety shower in close proximity to points of potential exposure.

Wear eye/face protection such as chemical splash proof goggles or face shield.

**Skin Protection:**

Prevent contamination of skin or clothing when removing protective equipment.

Wear impermeable gloves and suitable protective clothing.

**Additional Advice:**

Food, beverages, and tobacco products should not be carried, stored or consumed where this material is in use. Before eating, drinking or smoking, wash face and hands thoroughly with soap and water. It is recommended that a shower be taken after completion of work shift especially if significant contact has occurred. Work clothing should then be laundered prior to reuse. Street clothing should be stored separately from work clothing and protective equipment. Work clothing and shoes should not be taken home.

## Section 9: Physical and Chemical Properties

### Appearance

- Form : Liquid
- Color : Pale Straw Clear Liquid

### Safety data

- Flash point : > 100 °
- Vapor pressure : < 110 kPa at 50 °C
- Boiling point : > 35 °C
- Water solubility : Immiscible
- Viscosity, kinematic :  $\geq 7 \text{ mm}^2/\text{s}$  at 40 °C

## Section 10: Stability and reactivity Data

- Materials to avoid : Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.
- Hazardous decomposition products : Exposition to high temperatures may produce hazardous decomposition products such as: carbon dioxide, carbon monoxide, smoke and oxides of nitrogen (NO<sub>x</sub>).
- Thermal decomposition : Note: Stable under recommended storage and handling conditions (see section 7).
- Hazardous reactions : Polymerization occurs when exposed to white light, ultraviolet light or heat above 30 deg C  
Keep away from radical-forming starting agents, peroxides, strongly alkaline materials and reactive metals in order to avoid exothermic polymerization reactions.

## **Section 11: Toxicological Information**

Further information : The Preparation is classified according to the conventional method (calculation method of the EC-directive 88/379/EWG). The liquid splashed in the eyes may cause irritation and reversible damage.

Acrylic components of the preparation have irritating properties. Prolonged or repeated contact with the product may result in irritation of the mucous membrane and the skin, redness, blistering and desiccation of the skin.

Cases of allergic skin reactions have been observed.

The liquid splashed in the eyes may cause irritation.

Ingestion may cause collapse, severe respiratory difficulties and adverse effects on the central nervous system.

data for hexanedioldiacrylate:  
LD50/oral/rat/: > 5000 mg/kg  
LD50/dermal/rabbit: > 3000 mg/kg  
Primary irritation effects on skin/rabbit eye: not irritant (Draize test)  
Primary irritation effects on mucous membrane/rabbit eye: not Irritant  
Acute inhalation risk (rat; test results depending on toxicity and volatility): no mortality after exposition for 7 hours at 20°C in highly concentrated resp. saturated atmosphere.

## **Section 12: Ecological Information:**

### **Ecotoxicity effects**

### **Further information on ecology**

Additional ecological information : The product should not be allowed to enter drains, water courses or the soil.

## **Section 13: Disposal Consideration**

Contaminated packaging : Not correctly emptied containers and ink residues are hazardous waste.

Emptied containers should be supplied to scrap utilization resp. recycling.

Do not empty into drains.

Waste key for the unused product : Ink sludge containing dangerous substances

**Section 14: Transport Information**

**Land transport**

- *ADR:*  
Not classified as dangerous in the meaning of transport regulations.

**Sea transport**

- *IMDG:*  
Not classified as dangerous in the meaning of transport regulations.

**Air transport**

- *ICAO/IATA-DGR:*  
Not classified as dangerous in the meaning of transport regulations.

**Hazard class:** Class not regulated

**Section 15: Other Regulatory Information**

**Labeling according to EC Directives**

Hazardous components which must be listed on the label:

- Acrylate-Oligomers
- Acrylate-Oligomers
- Acrylate-Oligomers

Symbol(s)	: Xi	Irritant
R-pharse(s)	: R36/38 R43 R52/53	Irritating to eyes and skin. May cause sensitization by skin contact. Harmful to aquatic organisms may cause long-term adverse effects in the aquatic environment.
S-pharse(s)	: S24 S26  S37 S60	Avoid contact with skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable gloves. This material and its container must be disposed of as hazardous waste.



## **Section 16: Other Information**

### **Further information**

The information on this MSDS is based on the present state of our knowledge and on current EU and national laws.

The user's working conditions are beyond our knowledge and control.

It is always the responsibility of the user to take all necessary steps in order to fulfill the demands laid down in the local rules and legislation.

The information in this MSDS is meant as a description of the safety requirements of our product: it is not to be considered as a guarantee of the product's properties.

Text of R-phrases mentioned in Section-3

R36/38        Irritating to eyes and skin.

R43            May cause sensitization by skin contact.

R36/37/38    Irritating to eyes, respiratory system and skin.

R51/53        Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53        Harmful to aquatic organisms may cause long-term adverse effects in the aquatic environment.

R36            Irritating to eyes.

**This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Westtek Enterprises Private Limited. The data on the sheet is related to specific product designated herein. Westtek Enterprises Private Limited in assumes no legal responsibility for use or reliance upon these data.**