

TECHNICAL DATA SHEET

Product code & description:

WCO/10006 UV WESTACURE RC GLOSS VARNISH-HAB

Description:

WCO/10006 UV WESTACURE RC GLOSS VARNISH-HAB is a UV curable coating designed for roller coat application in-line over UV curable inks or off-line over dried conventional inks. It can be applied on a wide range of papers and boards. Product has good slip and surface wetting characteristics, high gloss, and good curing speed with improved anti-block property.

Technical Characteristics:

| | |
|----------------------------------|-------------------------|
| Application: | Roller Coater |
| Color & Appearance: | Pale straw liquid |
| Print Weight: | 4 to 6 g/m ² |
| Viscosity by Ford Cup B4 @ 30°C: | 40-55 sec |
| Dry Solid Content: | Aprox.100% |

NOTE: -

Preliminary adhesion tests are recommended prior to commercial run.
Always shake well before use.
Not recommended for foil stamping operation.
Avoid coating process on tonner-based oil based conventional ink printed Job.

Product safety:

This product is not recommended for low migration and low odor requirement.

The Printer/Converter/Packer have the legal responsibility to ensure that the finished article is fit for the intended purpose and that ink & coating components do not migrate into the food at levels that exceed legal and industry requirements.

Shelf life:

6 months from the date of manufacturing, if it is stored in sealed container below 25 °C away from heat & sunlight.

Precautions:

Avoid contact of UV Coating with skin and eyes. We recommend use of disposable gloves and protective goggle

Disclaimer:

This information is furnished without warranty, expressed, or implied, except that it is accurate to the best knowledge of Westtek Enterprises Private Limited. The data on the sheet is related to specific product designated herein. Westtek Enterprises Private Limited assumes no legal responsibility for use or reliance upon these data.