

## **TECHNICAL DATA SHEET**

**PRODUCT CODE: WCO/50021**

**PRODUCT DESCRIPTION: WESTACOAT RC MET PRIMER**

**WESTACOAT RC MET PRIMER:** It is a hi-tech water-based acrylic, ready to use primer for MET PET board substrate. It will help in inter-coat adhesion with UV ink & varnishes. The product has excellent gloss, adhesion and unique low foaming characteristics.

### **Technical Characteristic's:**

Application	Roller Coater MET-PET board for UV inks & varnish
Colour & Appearance	Semi translucent liquid
Viscosity by Ford Cup B4 @ 30°C	40 – 60 Sec
pH	7.5 - 9
Solid content	42±2 %
Print Tested in Lab	Using Bar Coater No.1 (Minimum film thickness applied 4 gsm)
Substrate	MET PET Board
Coating's Lay	Good
Adhesion	Good

**Note:** -

1. Preliminary adhesion tests are recommended prior to commercial run.
2. Always shake well before use.

**Shelf life:** WESTACOAT RC MET PRIMER can be stored at ambient temperature for 6 months. It should be stirred well with a wooded rod before use.

**Precautions:** WESTACOAT RC MET PRIMER is formulated keeping in consideration health & environmental aspects. It is non-inflammable, non-toxic & safe to use.

**Disclaimer:** This information is furnished without warranty, expressed, or implied, except that it is accurate to the best knowledge of Westtek Enterprises Private Limited. The data on the sheet is related to specific product designated herein. Westtek Enterprises Private Limited assumes no legal responsibility for use or reliance upon these data.